

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/056462 A1

(51) International Patent Classification⁷: **B01J 8/00**,
8/18, 8/24

(21) International Application Number:
PCT/EP2003/014105

(22) International Filing Date:
12 December 2003 (12.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 60 738.9 23 December 2002 (23.12.2002) DE

(71) Applicant (for all designated States except US): **OUT-OKUMPU OYJ [FI/FI]**; Riihitontuntie 7, FIN-02200 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FREYTAG, Jochen**

[DE/DE]; Waldstrasse 55, 61250 Usingen (DE). **HIRSCH, Martin** [DE/DE]; Am Vogelschutz 5, 61381 Friedrichsdorf (DE). **STRÖDER, Michael** [DE/DE]; Dürerstrasse 77, 61267 Neu-Anspach (DE).


(74) Agent: **KEIL & SCHAAFHAUSEN**; Cronstettenstrasse 66, 60322 Frankfurt am Main (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: METHOD AND PLANT FOR THE CONVEYANCE OF FINE-GRAINED SOLIDS



(57) Abstract: The present invention relates to a method for the conveyance of fine-grained solids in a fluidized bed reactor and also to a corresponding plant. It is proposed to introduce a first gas or gas mixture from below through a central tube (3) into a mixing chamber (7) of the reactor (1), the central tube (3) being at least partly surrounded by a stationary annular fluidized bed (10) which is fluidized by supplying fluidizing gas. The gas velocities of the first gas or gas mixture as well as of the fluidizing gas for the annular fluidized bed (10) are adjusted such that the particle Froude numbers in the central tube (3) are between 1 and 100, in the annular fluidized bed (10) between 0.02 and 2 in the mixing chamber (7) between 0.3 and 30.



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*